

Welding & Cutting Outfit ACCESSORIES



Welding Tip
HCW-W0



Welding Tip
HCW-W1



Welding Tip
HCW-W2



Welding Tip
HCW-W3



Welding Tip
HCW-W4



Welding Tip
HCW-W5



Welding Tip
HCW-W6



Welding Tip
HCW-W7



Welding Tip
HCW-W8



Welding Tip
HCW-W9



Welding Tip
HCW-W10



Cutting Nozzle
6290-1
Acetylene



Cutting Nozzle
6290-NX1
Propane



MIXER
Type:E2-43
ACETYLENE



Check Valve
88-3FGR



Check Valve
88-3FGL



Flashback Arrestor
188-R OXYGEN(9/16"x18R.H)
FOR TORCH



Flashback Arrestor
188-L ACETYLENE(9/16"x18L.H)
FOR TORCH



Tip Cleaners
IO-TC13G



Sparklighter
26-S



Twin Hose 15ft with Fitting
IO-HSGR



Torch Handle
HC63-2



Cutting Attachment
HC73-2



Regulator
OR-25 (25-7)
Oxygen



Regulator
AR-25 (25-1.4M)
Acetylene



Goggles
IO-GGFB

WELDING MACHINE

DC INVERTER WELDER

Made in Taiwan



MMA168

3 meters cable + Electrode Holder
2 meters cable + Earth Clamp



ARC-200

20-180A



ARC-250

20-220A



- **Super Lightweight**
- **High efficiency, high quality, stable arc.**
- **Arc power and anti freeze are standard facilities.**
- **Suitable for welding of low carbon steel, cast iron, low alloy and stainless steel.**

Model	MMA168	ARC-200	ARC-250
Power Voltage (V)	1 Phase AC220V ± 10%	1 Phase AC220V ± 15%	1 Phase AC220V ± 15%
Frequency (Hz)	60	60	60
Rated Input Current (A)	28	41	55
No-Load Voltage (V)	56	85	85
Output Current (A)	20-150	20-200	20-250
Rated Output Voltage (V)	25.4	28	30
Duty Cycle (%)	80	80	80
No-load loss (W)	40	40	60
Stick Diameter (mm)	2.0-3.2	-----	-----
Efficiency (%)	85	80	85
Power Factor	0.93	0.73	0.93
Insulation Grade	F	F	F
Housing Protection Grade	IP23	IP28	IP28
Weight (kg)	3.8	8.7	8.7
Dimensions (mm)	283 x 150 x 259	342 x 140 x 229	342 x 140 x 229